

# CHALLENGER 4 TEMPS 15W-40

*Mineral 4 strikes Engine Oil for motorbikes*

## SPECIFICATIONS

✓ API SL

## APPLICATIONS

**CHALLENGER 4 TEMPS 15W-40** is a mineral 4 strikes Engine oil suitable for Motorbikes engines requiring lubricants meeting API SL specification.

**CHALLENGER 4 TEMPS 15W-40** is particularly adapted to extremely severe use under very hot climates.

## MAIN PROPERTIES

**CHALLENGER 4 TEMPS 15W-40** selection of detergent & dispersing agents ensures a perfect cleanliness of the engine.

**CHALLENGER 4 TEMPS 15W-40** keeps a perfect stability in time which gives it long life performances.

## TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUE	METHODS
SAE Grade		<b>15W-40</b>	
Specific gravity at 20°C	kg/m <sup>3</sup>	868	NFT 60101
Kin. Viscosity at 40°C	mm <sup>2</sup> /s	107,5	NFT 60100
Kin. Viscosity at 100°C	mm <sup>2</sup> /s	14,4	NFT 60100
Viscosity index		137	NFT 60136
Flash point	°C	234	NFT 60118
Pour point	°C	-43	NFT 60105
Sulphated Ash	%	1.4	DIN 51575
T.B.N.	mgKOH/g	10.4	NFT 60112