

COFRAGREASE EPC 3

**Multifunctional EP industrial grease for all organs subjected to extreme pressure.
Can also be used in vehicles and public works equipment.**

APPLICATIONS

For all bearings under load and which are subjected to shocks or are working in severe conditions, i.e., lubrication of public works vehicles, masts of fork-lift trucks racks of heavy equipment, etc...

PROPERTIES

- Multipurpose grease
- Temperature resistant
- Water resistant
- Ageing resistant
- Good corrosion protection
- Good adhesion
- Good antiwear properties
- Good pumpability

TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUES	METHODS
Classification		KP3K-30 ISO-L-X-CCEA 2	DIN 51502 ISO 6743-9
NLGI Grade		3	
Color		Amber	
Type of soap		Lithium	
Texture		Smooth	
Penetration worked (60x)	0.1mm	220/250	DIN/ISO 2137
Flash Point	°C	230	ASTM D93
Pour Point	°C	195	ASTM D566
EP Properties : 4 balls tests (welding load)	Kg	230	IP 239
Water resistance	Stage	janv-90	DIN 51 807-1
Base oil 40°C viscosity	mm ² /s	110	DIN 51 562-1
Base oil 100°C viscosity	mm ² /s	9.5	DIN 51 562-1
Corrosion protection	Corrosion degree	0 - 0	DIN 51 802
Temperatures range	°C	-30 à +120	DIN 51 825