

COFRAGREASE MULTI B2

Multipurpose grease for usual lubrication of automotive and industrial equipment.

APPLICATIONS

- Lubrication of automotive bearings
- Lubrication of industrial bearings and joints, or mechanical organs working under light or medium load.

MAIN PROPERTIES

- Share stability as for chemical and heating
- Water-resistant
- Anti-corrosion and anti-oxidation properties

- Temperature range : - 30°C to 120°C.

TECHNICAL CHARACTERISTICS

| AVERAGE CHARACTERISTICS | UNIT | AVERAGE VALUES | METHODS |
|-----------------------------------|--------------------|-----------------------|----------------|
| Product Classification | | K2K-30 | DIN 51825 |
| NLGI Grade | | 2 | |
| Colour | | Amber | |
| Thickening Agent | | Lithium | |
| Texture | | Smooth | |
| Dropping Point | °C | 195 | ASTM D566 |
| Flash Point | °C | 230 | ASTM D93 |
| Worked penetration 60 Strokes | mm/10 | 280 | ASTM D217 |
| | 100 000 Strokes | 7% | |
| EP properties : 4 balls weld load | Kg | 230 | ASTM D 2596 |
| Base Oil viscosity at 40°C | Mm ² /s | 100 | ASTM D 445 |
| | at 100°C | 10 | |