

## **COFRAN ATF 4000**

*Lubricant for passenger cars or heavy vehicles automatic gear-boxes & power steerings*

### **SPECIFICATIONS :**

COFRAN ATF 4000 meets the requirements :

**GM DEXRON III (H)**  
**ALLISON C4 / TES-389 - ZF TE-ML 02F/03D/04D/09/11B/14A/17C**  
**BMW - CATERPILLAR TO-2 - FORD MERCON - MAN 339 Type L-1/V-1/Z-1**  
**MB 236.1 / 236.9 - VOLVO 97340/97341 - VW TL 521 62 (G 052 162)**  
**VOITH 55.6335.XX (G607) -**

### **ADVANTAGES :**

COFRAN ATF 4000 is a mineral base-oil lubricant with specific additives that allows :

- . Excellent stability against oxidation;
- . Good share stability and heavy load resistancy;
- . Increased anti-wear and anti-foam properties.

### **APPLICATIONS :**

- . Automatic transmissions (and some mechanical gear-boxes);
- . Power steering;
- . Hydraulic clutches;
- . Torque convectors and some hydraulic systems;
- . Mainly, all equipment where an ATF Dexron II E and III is recommended
- . Must not be used in case of a GM Type A Suffix A recommendation

### **TECHNICAL CHARACTERISTICS:**

<b>AVERAGE CHARACTERISTICS</b>	<b>UNIT</b>	<b>AVERAGE VALUE</b>	<b>METHODS</b>
Colour		Red	
Density at 20°C	kg/m <sup>3</sup>	848	NFT 60101
Viscosity at 40°C	mm <sup>2</sup> /s	36	NFT 60100
Viscosity at 100°C	mm <sup>2</sup> /s	7,55	NFT 60100
Viscosity index		186	NFT 60136
Flash Point	°C	234	NFT 60118
Pour Point	°C	-54	NFT 60105