

COFRAN ATF 4400

Lubricant for automatic gear-boxes of vehicles equipped with AISIN WARNER gearboxes

NORMS & SPECIFICATIONS

Specifications :

- JASO M315 TYPE 1A

Recommandations :

- DEXRON III (H)
- BMW MINI 83220402413 / 83227542290
- CHRYSLER MS7176E/9602 (ATF +3/+4)
- DAIHATSU ALUMIX ATF MULTI
- FIAT 9.55550-AV1/AV4
- FORD MERCON / MERCON V
- FORD M2C 922-A1 / 924-A
- FORD WSS-M2C919-E / M2C202-B
- GM 9986195
- HONDA ATF Z-1
- HYUNDAI SP III
- ISUZU BESCO ATF-II/-III
- JATCO 3100PL085 / FWD (N402) / JF506E (K17)
- JWS 3309/ TYPE T-IV
- MAZDA ATF D-III/ATF M-3/ATF M-V
- MITSUBISHI SP-II/-III
- NISSAN MATIC C/D/J
- SAAB 3309
- SUBARU ATF OIL/ ATF OIL SPECIAL/ ATF HP
- SUZUKI ATF 3309/ 3317
- TOYOTA TYPE T/ T-II/ T-III/ T-IV
- TOYOTA TYPE D-2
- VW G 052 990 / 055 025

APPLICATIONS

COFRAN ATF 4400 is designed to be used in AISIN WARNER automatic gearboxes. These gearboxes are used in many Japanese cars and commercial vehicles but also in many European and American models.

COFRAN ATF 4400 can be used in many Japanese vehicles and when oil type Dexron III is recommended.

COFRAN ATF 4400 is miscible and compatible with conventional automatic transmissions oils. However, we recommend to avoid mixing with other transmission oil so as not to degrade the properties of **COFRAN ATF 4400**.

TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUE	METHODS
Colour		Red	
Density at 20°C	kg/m ³	845	NFT 60101
Viscosity at 40°C	mm ² /s	34	NFT 60100
Viscosity at 100°C	mm ² /s	6.8	NFT 60100
Viscosity Index		162	NFT 60136
Flash Point	°C	206	NFT 60118

MAIN PROPERTIES

- Excellent properties at cold start
- High friction level, stable over the lifetime of the product
- Excellent anti-wear protection for better reliability
- Excellent oxidation stability and resistance to the aging of the lubricant



Les renseignements contenus dans cette notice sont donnés à titre indicatif. Nous nous réservons le droit d'apporter, sans préavis, toutes modifications à la formulation de nos produits dans le but d'en améliorer les performances ou de les mettre en conformité avec toute nouvelle et éventuelle réglementation les concernant.