

COFRAN ATF 6000

Synthetic lubricant for automatic gearboxes and power steering formulated according to the specifications DEXRON VI / FORD MERCON LV / JASO M315 TYPE 1A-LV

SPECIFICATIONS

- DEXRON VI
- FORD MERCON LV
- JASO M315 TYPE 1A-LV
- AISIN WARNER/AW-1
- BMW 81 22 9 400 272
- BMW 81 22 9 400 275
- BMW 81 22 9 407 738
- BMW 83 22 0 397 114
- BMW 83 22 0 403 248
- BMW 83 22 0 403 249
- BMW 83 22 0 432 807
- BMW 83 22 2 163 514
- BMW 83 22 2 167 718
- BMW 83 22 2 167 720
- BMW 83 22 2 355 599
- BMW 83 22 2 355 601
- BMW 83 22 9 407 858
- BMW 83 22 9 407 859
- FIAT 9.55550-AV2 / AV6
- GM 9256039/88863400
- HONDA DW-1
- HYUNDAI NWS 9638
- HYUNDAI SP-IV / SP-IV M / SP-IV RR
- JWS 3324
- KIA SP-IV
- MITSUBISHI ATF-J3 / ATF-PA / MA1
- NISSAN MATIC S
- TOYOTA TYPE WS
- VW G 055 540 A2
- ZF TE-ML 09

MAIN PROPERTIES

- Improved gearshift performance compared to conventional oils ATF
- High protection against wear, improved automatic transmission lifetime
- Very good stability against oxidation
- Oil drain recommendation : more than 1.000.000 Km

TECHNICAL CHARACTERISTICS

CHARACTERISTICS	UNIT	AVERAGE VALUE	METHOD
Color		Red	
Density at 15°C	kg/m ³	851	
Viscosity at 40°C	mm ² /s	29.0	DIN 51562-1
Viscosity at 100°C	mm ² /s	6.0	DIN 51562-1
Viscosity Index		155	DIN ISO 2909
Flash point	°C	202	DIN ISO 2592
Pour point	°C	-48	DIN ISO 3016

APPLICATION

COFRAN ATF 6000 is a synthetic ATF lubricant for the last generation of automatic gearboxes & power steering of the Asian & Americans vehicles