

COFRAN DCTF DSG

DCTF lubricant for double clutch transmissions with wet clutches

SPECIFICATIONS

Recommandations :

- BMW Drivelogic 7-speed
- Chrysler Powershift 6-speed
- FORD Powershift 6-speed
- Mitsubishi TC-SST 6-speed
- Peugeot DCS 6-speed
- Citroën DCS 6-speed
- RENAULT EDC 6-speed
- Volvo Powershift 6-speed
- VW 6-speed FWD

PROPERTIES & ADVANTAGES

- Outstanding friction characteristics and stability over the whole drain interval.
- Offers best shifting properties even under severe conditions.
- Optimum anti wear performance.
- Best oxidation stability.
- Excellent protection against corrosion.
- Very good behaviour at low temperatures.
- Ultra versatile products with proven performances.

APPLICATIONS

COFRAN DCTF DSG was specially developed for use in wet double clutch transmissions.

All key performance tests conducted have proved that **COFRAN DCTF DSG** has better performances than the reference fluids

TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUE	METHODS
Colour		Amber	
Density at 15°C	kg/m ³	849	NFT 60101
Viscosity at 40°C	mm ² /s	33.2	NFT 60100
Viscosity at 100°C	mm ² /s	7,1	NFT 60100
Viscosity Index		185	NFT 60136
Flash Point	°C	210	NFT 60118
Pour Point	°C	- 45	NFT 60105