

COFRAN DCTF DSG

DCTF lubricant for double clutch transmissions with wet clutches

SPECIFICATIONS

Recommandations :

- **BMW 83 22 2 148 578**
- **BMW 83 22 2 148 579**
- **FORD WSS M2C 200 D2**
- **FORD WSS M2C 936-A**
- **MITSUBISHI DIA QUEEN SSTF-1**
- **PSA 9734 S2**
- **VW TL 52 182 (G 052 182)**

PROPERTIES & ADVANTAGES

- Outstanding friction characteristics and stability over the whole drain interval.
- Offers best shifting properties even under severe conditions.
- Optimum anti wear performance.
- Best oxidation stability.
- Excellent protection against corrosion.
- Very good behaviour at low temperatures.
- Ultra versatile products with proven performances.

APPLICATIONS

COFRAN DCTF DSG was specially developed for use in wet double clutch transmissions.

All key performance tests conducted have proved that **COFRAN DCTF DSG** has better performances than the reference fluids

TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUE	METHODS
Colour		Amber	
Density at 15°C	kg/m ³	849	NFT 60101
Viscosity at 40°C	mm ² /s	33.2	NFT 60100
Viscosity at 100°C	mm ² /s	7,1	NFT 60100
Viscosity Index		185	NFT 60136
Flash Point	°C	210	NFT 60118
Pour Point	°C	- 45	NFT 60105