

COFRAN LF DOT 4

High Performance brake fluid for hydraulic brake and clutch systems in vehicles & industrial machinery.

SPECIFICATIONS

• Meets the requirements :

- ✓ FMVSS 116 DOT 3 / DOT 4
- ✓ SAE J 1703 / J 1704
- ✓ ISO 4925
- ✓ NFR 12640

APPLICATIONS

- For hydraulic brakes and clutch systems in vehicles and industrial machinery,
- Optimal use even under very severe conditions (competition,...),
- Miscible with brake fluid using the same technology (DOT 3 - 4 - 5.1),
- Do not use when the manufacturer recommends a mineral brake fluid such as LHM Citroën.
- Not miscible with the fluid LOOCKEED HD 12.

PROPERTIES

- High quality and long life. Thermally and chemically stable even after long periods of use and high thermal loads.
- Outstanding performance reserves. The wet boiling point means unsurpassed safety even in the most difficult conditions
- Outstanding protection against wear.
- Protects against corrosion, sludging & gumming on pistons & valves.
- Absolute reliability at all temperatures. No leakage from systems designed to operate on DOT 3/DOT 4 brake fluids.
- Compatible with all hoses, gaskets and seals.

TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUES
Color		Amber
Specific Gravity at 20°C	kg/m ³	1050
Dry boiling point	°C	>260
Wet boiling point	°C	>180