

## **COFRAN LF DOT 5.1**

**High Performance brake fluid for hydraulic brake and clutch systems in vehicles & industrial machinery.**

### **SPECIFICATIONS**

- ✓ FMVSS 116 DOT 5.1 / DOT 4 / DOT 3
- ✓ SAE J 1703
- ✓ ISO 4925
- ✓ NFR 12640

### **APPLICATIONS**

- For hydraulic brakes and clutch systems in vehicles and industrial machinery,
- Optimal use even under very severe conditions (competition,...),
- Miscible with brake fluid using the same technology (DOT 3 - 4 - 5.1),
- Do not use when the manufacturer recommends a mineral brake fluid such as LHM Citroën.
- Not miscible with the fluid LOOCKEED HD 12.

### **PROPERTIES**

- High quality and long life. Thermally and chemically stable even after long periods of use and high thermal loads.
- Outstanding performance reserves. The wet boiling point means unsurpassed safety even in the most difficult conditions
- Outstanding protection against wear.
- Protects against corrosion, sludging & gumming on pistons & valves.
- Absolute reliability at all temperatures. No leakage from systems designed to operate on DOT 3/DOT 4 brake fluids.
- Compatible with all hoses, gaskets and seals.

### **TECHNICAL CHARACTERISTICS**

<b>AVERAGE CHARACTERISTICS</b>	<b>UNIT</b>	<b>AVERAGE VALUES</b>
Specific Gravity at 20°C	kg/m <sup>3</sup>	1060 to 1080
Kynematic viscosity at 40°C	Mm <sup>2</sup> /s	900
Dry boiling point	°C	>260
Wet boiling point	°C	>180