
COFRAN SUPER DKP

Cleaning and degreasing oil for metal parts with high solvent power.

PROPERTIES

- Antiseptic, COFRAN SUPER DKP disinfects and cleans.
- Non toxic – does not release toxic smokes
- Emulsifies in water and eliminates grease and fats.
- Anti-rust and corrosion, protects parts after treatment.

APPLICATIONS

- . Degreasing before electrolytic treatment.
- . Degreasing before painting, cleaning of brushes.
- . Cleaning of parts protected by wax.
- . Cleaning of tar on bodywork.
- . Cleaning of floor.

HOW TO USE

- Degreasing of small parts, by dipping for 15 minutes. Allow to drain and clean with water.
- COFRAN SUPER DKP emulsifies and takes away all greases fats and other dirt. If necessary dry with compressed air.
- For large parts, spray with an air pistol. Allow to work for 15 minutes and rinse with water jet.
- Floors : spread lightly on the floor to be treated. Wait 15 minutes. Rinse abundantly with water. For particularly dirty floors, repeat the operation a few days later.
- COFRAN SUPER DKP is according to the Law in force.

TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUES	METHODS
Specific Gravity at 20°C	kg/m ³	833	NFT 60101
Flash Point	°C	77	
Kynepatic viscosity at 20°C	mm ² /s	3,23	NFT 60100
Kynematic viscosity at 25°C	mm ² /s	2,80	NFT 60100