

MOTONAUTIC 3

Semi-synthetic ashless 2-stroke oil for all outboard engines, with direct injection or not.

NORMS & SPECIFICATIONS

• Meets the specification :

✓ NMMA TC-W3 RL

MAIN PROPERTIES

Prevents carbon deposits, spark plug fouling and ring sticking.

Pre-diluted. For oil injection systems and premix. Usable with unleaded petrol.

- Very high protection against wear & corrosion.
- No deposit in cylinders, on pistons, valves & spark plugs.
- Very good protection against pistons clamping.
- Low viscosity ensuring excellent & stable mix.
- Easy identification thanks to its red colour.

APPLICATIONS

MOTONAUTIC 3 formula enables its use on outboard engines :

- Of all powers from 5 to 250 Hp +.
- At all engines speeds.
- for short or long duration service.
- As a mix or on separate lubrication.

Fuel/oil ratio : mix according to manufacturer's recommendations.

TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUE	METHODS
Colour		Red	
Specific gravity at 20°C	kg/m ³	865	NFT 60101
Viscosity at 40°C	mm ² /s	41,7	NFT 60100
Viscosity at 100°C	mm ² /s	7,2	NFT 60100
Viscosity Index		≥130	NFT 60136
T.B.N.	mgKOH/g	10,59	ASTM D2896