

PLURA 20W-50

Lubricant multigrade for petrol and diesel engines even when turbo charged.

SPECIFICATIONS

- Meets the specifications :
 - ✓ ACEA A3/B3/B4/E2
 - ✓ API SL/CF/CG-4
- OEM performance level :
 - ✓ MACK EO-L
 - ✓ MAN 271
 - ✓ MB p.228.1
 - ✓ MTU DDC Type-2
 - ✓ VOLVO VDS

APPLICATIONS

PLURA 20W-50 is the ideal lubricant for fleets of vehicles where simplification is required.

When you need a lubricant, which can be used for diesel engines as well as for petrol engines, PLURA 20W-50 meets the requirements for performance and engine efficiency for both types.

With PLURA 20W-50, COFRAN can offer you a predictive engine monitoring service by regular analyses of the lubricant in use. Your sales agent will help you to get the monitory logistics ready.

MAINT PROPERTIES

Owing to its detergent properties, **PLURA 20W50** ensures an effective dispersion of combustion residues and accumulated deposits, thus maintaining engines high operating performance.

PLURA 20W-50 is extremely sheared resistant, ensuring a constant lubrication of operating parts and optimizing the properties of anti-wear additives.

TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUE	METHODS
SAE Grade		20W-50	
Specific Gravity at 20°C	kg/m ³	886	NFT 60101
Viscosity at 40°C	mm ² /s	166	NFT 60100
Viscosity at 100°C	mm ² /s	18,3	NFT 60100
Viscosity index		≥ 120	NFT 60136
Flash Point	°C	≥ 230	NFT 60118
Pour Point	°C	-24	NFT 60105
TBM	mgKOH/g	8.72	ASTM D2896