

PLURA EXTREME 15W-40

Long life high quality Diesel Engine Oil made with synthesis MC base oils reinforced in TBN for use in countries with high sulphur content diesel

SPECIFICATIONS

• Specifications :

- ✓ ACEA E7
- ✓ API CI-4/SL
- ✓ GLOBAL DHD - 1

• Recommendations :

- ✓ ALLISON C 4
- ✓ CASE MS 1121
- ✓ CAT ECF-1a / ECF-2 / TO2
- ✓ CUMMINS CES 20071/72/76/77/78
- ✓ DETROIT DIESEL 93K215
- ✓ DEUTZ DQC III
- ✓ IVECO 18-1804 CLASSE T2 E7
- ✓ MACK EO-N
- ✓ MAN M 3275-1
- ✓ MB p.228.3
- ✓ MTU DDC Type 2
- ✓ NH 330 H
- ✓ RENAULT RLD/RLD-2
- ✓ VOLVO VDS-3

APPLICATIONS

PLURA EXTREME 15W-40 answers to the requirements of the diesel engines with direct injection, turbochargers etc... It is suitable up to EURO 4 engines.

PLURA EXTREME 15W-40 has been specially developed to be used in countries where the diesel has a high sulphur content.

MAIN PROPERTIES

PLURA EXTREME 15W-40 is a product of the most advanced technology. The selection of its detergent & dispersing agents ensures a perfect cleanliness of the engine.

PLURA EXTREME 15W-40 keeps a perfect stability in time which gives it long life performances.

PLURA EXTREME 15W-40 high TBN of 15 enables to fight the acidity created by the combustion of the high sulphur content diesel and to protect better the engine.

TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUE	METHODS
SAE Grade		15W-40	
Specific gravity at 20°C	kg/m ³	886	NFT 60101
Kin. Viscosity at 40°C	mm ² /s	109	NFT 60100
Kin. Viscosity at 100°C	mm ² /s	14,9	NFT 60100
Viscosity index		140	NFT 60136
Flash point	°C	230	NFT 60118
Pour point	°C	-36	NFT 60105
Sulphated Ash	%	2	DIN 51575
T.B.N.	mgKOH/g	15	NFT 60112