

PLURA PLUS 15W-40

High performance lubricant for diesel & gasoline engines even turbocharged, adapted for severe conditions

APPLICATIONS

With its reinforced properties, **PLURA PLUS 15W40** is particularly adapted for warm and moist countries. It can be used for engine trucks, generators, earthmoving materials etc... It is also adapted for gasoline engine allowing to simplify fleet maintenance.

ADVANTAGES

PLURA PLUS 15W40 offers a high protection against the wear of pistons liners.
PLURA PLUS 15W40 has an effective detergent, a high shear resistance & reinforced antiwear properties
PLURA PLUS 15W40 remains always in grade during its life, reducing wears at low starting temperature.

NORMS & SPECIFICATIONS

Cofran Recommendations :
API CH-4/SL/CF
CATERPILLAR ECF-1a
CUMMINS CES 20076
MACK EO-M+
MAN 3275
MB p228.3
RENAULT RD/RD-2
VOLVO VDS-2

TECHNICAL CHARACTERISTICS

AVERAGE TECHNICAL CHARACTERISTICS	UNITS	AVERAGE VALUE	TEST METHOD
SAE Grade		15W-40	
Specific gravity at 20°C	kg/m ³	873	NFT 60101
Kinematic viscosity at 40°C	mm ² /s	102	NFT 60100
Kinematic viscosity at 100°C	mm ² /s	14,2	NFT 60100
Viscosity index		141	NFT 60136
Flash Point	°C	238	NFT 60118
TBN	Mg/KOH/g	10.4	ASTM D2896

Characteristics are given as an indication.