

PLURA STOU 15W-40

Multifunctional lubricant for Agriculture or Public Works Equipment for engines, for mechanical & hydraulic transmissions and for wet brakes

SPECIFICATIONS

Specifications :

- ACEA E3
- API CF-4
- API GL-4
- SAE J300 : 15W-40
- SAE J306 : 80W-90

Recommandations :

- DIN 51524 : HLP (-D)
- CNH MAT 3525 / 3526
- FENDT KDM 17/2012
- FNHA 200.00, 201.00
- FORD M2C134-D
- FORD M2C159-B/C
- JOHN DEERE JDM J20C
- MF CMS 1145 (1135 1139 1143 1144)
- NEW HOLLAND 82009201 / 2 / 3
- NH 420 A
- SDFG OU 1391, OT 1891
- STEYR D-401
- ZF TE-ML 06A, 06B, 06C, 07B

APPLICATIONS

PLURA STOU 15W-40 is particularly adapted for the lubrication of mixed-fleet like in agriculture (tractors, harvesters, threshers etc.) but its multifunction allows the usage in the public-works having similar fleet like agriculture.

PLURA STOU 15W-40 can lubricate parts of agriculture engines, vehicles of road-works & vehicles of transport :

- Petrol & Diesel engines
- Mechanical transmissions, Wet brakes, Gear-boxes & reducers
- Hydraulic circuits & hydrostatic transmissions

MAIN PROPERTIES

- All-season suitability (engine, gearbox, hydraulic)
- Miscible with other engine or gear oils of same specification
- Reduced inventory

TECH CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUES	METHODS
SAE Grade		15W-40	
Density at 20°C	kg/m ³	890	NFT 60101
Viscosity at 40°C	mm ² /s	102	NFT 60100
Viscosity at 100°C	mm ² /s	13,85	NFT 60100
Viscosity Index		137	NFT 60136
Flash Point	°C	222	NFT 60118
Pour Point	°C	-30	NFT 60105