

---

## **PLURAFLUID P**

---

*High performance lubricant for hydraulics systems.*

### **MAIN PROPERTIES**

Due to a high stable and specific formulation, **PLURAFLUID P**, has a high shear stability and low viscosity at low temperature.

### **SPECIFICATIONS**

- AFNOR NFE 48603 HV
- CATERPILLAR, MANITOU, CASE POCLAIN, SAMBRON...

### **APPLICATIONS**

Hydraulic lubricant specially recommended for hydraulics systems, of public works equipments, such as : crawlers, bulldozers, loaders, forklift...

### **TECHNICAL CHARACTERISTICS**

<b>AVERAGE CHARACTERISTICS</b>	<b>UNIT</b>	<b>AVERAGE VALUES</b>	<b>METHODS</b>
ISO Grade		<b>46</b>	
Colour		Blue	
Density at 20°C	kg/m <sup>3</sup>	874	NFT 60101
Viscosity at 40°C	mm <sup>2</sup> /s	47,05	NFT 60100
Viscosity at 100°C	mm <sup>2</sup> /s	9,70	NFT 60100
Viscosity index		197	NFT 60136
Flash Point	°C	200	NFT 60118
Pour Point	°C	-36	NFT 60105

Characteristics are given as an indication