

PLURAMATIC UTTO J20C

High-performance lubricant recommended for public work transmissions equipped with gears and immersed disk brakes (box assemblies, axles, lifting devices, immersed brakes in agricultural tractors, civil engineering tractor loaders and work site fork lift trucks)

NORMS & SPECIFICATIONS

Specifications :

- **SAE J300 : 10W-30**
- **SAE J306 : 75W-80**
- **API GL-4**
- **ISO VG 32-68**

Recommandations :

- **AGCO Powerfluid 821 XL**
- **AGCO Q-186 (Whitefarm)**
- **ALLISON C-4**
- **CASE MS 1206/1207/1209/1210/1230**
- **CLASS/LANDINI/SAME Transmission**
- **CNH MAT 3526 / 3525 / 3510 / 3509 / 3506 / 3505**
- **FNHA-2-C-200 00 / 201 00**
- **FORD M2C 86-B/C**
- **FORD M2C 134-D**
- **JOHN DEERE JDM J20C**
- **MF CMS 1135/1141/1143/1145**
- **NH 410 B**
- **SDFG OT 1891 A**

MAIN PROPERTIES

- Prevents the formation of deposits, gumming, varnishes and other types of sediment
- Excellent protection against corrosion,
- Reduces noise and grinding of immersed brakes; it is also compatible with seals and non-ferrous materials normally used in transmissions,
- Excellent cold and hot lubrication, even at low temperature,
- Oil for agricultural machinery and public works in any season,
- Ensures the reliability of immersed brakes and differentials, as well as synchronised systems, even under severe loads.

APPLICATIONS

PLURAMATIC UTTO J20C is an alternative for replacing grade 10W-30 multifunctional lubricants or grade 75W-80 API GL4 gearbox oils in the transmissions of agricultural tractors or public works.

- It is more suitable to use **PLURAMATIC UTTO J20C** in different components of motors (hydraulic, transmission, box, axle) and this avoids malfunction. It also replaces engine lubricants which are used in hydraulic circuits.

TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUES	METHODS
Density at 20°C	kg/m ³	876	NFT 60101
Viscosity at 40°C	mm ² /s	61.25	NFT 60100
Viscosity at 100°C	mm ² /s	9.65	NFT 60100
Viscosity Index		135	NFT 60136
Pour Point	°C	-36	NFT 60105