

PLURAMATIC UTTO WB

High-performance lubricant recommended for public work transmissions equipped with gears and immersed disk brakes

SPECIFICATIONS

Specifications :

- **API GL-4**
- **SAE J300 : 10W-30**

Recommandations :

- **AGCO Powerfluid 821 XL**
- **AGCO Q-186 (Whitefarm)**
- **ALLISON C-4**
- **CASE MS 1204/1205/1206/1207/1209 / 1210**
- **CATERPILLAR TO-2**
- **CNH MAT 3505 / 3506 / 3525**
- **FNHA-2-C-201 00**
- **FORD M2C 41B/53B/92A/134D**
- **JOHN DEERE JDM J20C**
- **KUBOTA UDT FLUID**
- **MF CMS 1135/1141/1143/1145**
- **VOLVO WB 101**
- **ZF TE-ML 03E/03F/03L/05F/06K**

MAIN PROPERTIES

- Prevents the formation of deposits, gumming, varnishes and other types of sediment
- Excellent protection against corrosion
- Reduces noise and grinding of immersed brakes; it is also compatible with seals and non-ferrous materials normally used in transmissions,
- Excellent cold and hot lubrication, even at low temperature
- Oil for agricultural machinery and public works in any season
- Ensures the reliability of immersed brakes and differentials, as well as synchronised systems, even under severe loads.

APPLICATIONS

PLURAMATIC UTTO WB is an alternative for replacing grade 10W-30 multifunctional lubricants or grade 75W-80 API GL4 gearbox oils in the transmissions of agricultural tractors or public works.

- It is more suitable to use **PLURAMATIC UTTO WB** in different components of motors (hydraulic, transmission, box, axle) and this avoids malfunction. It also replaces engine lubricants which are used in hydraulic circuits.

TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUES	METHODS
Density at 15°C	kg/m ³	870	DIN 51757
Viscosity at 40°C	mm ² /s	65.3	DIN 51562-1
Viscosity at 100°C	mm ² /s	10.2	DIN 51562-1
Viscosity Index		170	DIN ISO 2909
Pour Point	°C	-48	DIN ISO 3016