

SINTOLUX FORCE 3 5W-40

Low SAP Synthetic Engine Oils for passenger cars

SPECIFICATIONS

Specifications	ACEA C3 API SN/CF
Approvals	BMW LONGLIFE 04 MB APPROVAL 229.52
Recommandations	CHRYSLER MS-10725 FIAT 9.55535-GH2/S2/T2 FORD WSS-M2C917-A MB 226.5 / 229.31 / 229.51 PORSCHE C40 RENAULT RN0700/RN0710 VW 505.00 / 505.01 / 511.00

PROPERTIES

- Excellent wear protection even under permanent load with maximum power output.
- Applicable in Diesel, gasoline and gas engines. Reduction in air pollutant emissions.
- Inhibits deposits in engines and turbochargers, thus excellent operation reliability and reduced maintenance costs.
- Low oil consumption due to minimum evaporative loss.
- Optimum cold starting, lower oil consumption and minimized exhaust emissions.

APPLICATIONS

SINTOLUX FORCE 3 5W-40 is a top of the range 5W-40 engine oil, featuring many of the latest specifications from the german car manufacturers (BMW, Mercedes-Benz and VW). It is also suitable for many other vehicles.

SINTOLUX FORCE 3 5W-40 fulfils engine oil requirements for vehicles with modern exhaust gas after treatment systems.

TECHNICAL CHARACTERISTICS

Average Characteristics	Unit	Average Value
SAE Grade		5W-40
Density at 15°C	kg/m ³	850
Viscosity at 100°C	mm ² /s	13.1
Viscosity at 40°C	mm ² /s	72.6
Viscosity Index		185
Pour Point	°C	- 42