

SINTOLUX FORCE 4 5W-30

Low SAP Engine Oil for Renault/Nissan passenger cars and others

SPECIFICATIONS

Specifications	ACEA C3 / C4
Recommandations	FIAT 9.55535-S4 MB 226.51 / 229.51 RENAULT RN 0720

APPLICATIONS

Developed specially for Renault and Nissan vehicles with exhaust post treatment and turbocharger until 2017

This very high performing fuel efficient Motor oil of SAE 5W-30 viscosity class is recommended to be used all over the year. Oil related residues in particulate filters will be reduced to an absolute minimum.

The fuel consumption can be significantly reduced by using **SINTOLUX FORCE 4 5W-30**.

SINTOLUX FORCE 4 5W-30 provides perfect pump ability at nearly all temperatures which protects of wear and lowers friction.

PROPERTIES

- Extended life time of particulate filters,
- Absolute perfect cold start behaviour,
- Significant lower fuel consumption at all running conditions,
- Low SAP's provides reduced exhaust gas back pressure,
- Perfect oxidative stability over the whole oil drain interval,
- Very low oil consumption,
- High effective wear protection is extending the engine life time.
- Optimum cold starting, lower oil consumption and minimized exhaust emissions.

TECHNICAL CHARACTERISTICS

Average Characteristics	Unit	Average Value
SAE Grade		5W-30
Density at 15°C	kg/m ³	850
Viscosity at 100°C	mm ² /s	12.07
Viscosity at 40°C	mm ² /s	65.44
Viscosity Index		172
Pour Point	°C	- 39
Flash Point	°C	239