

SINTOLUX FORCE F 5W-20

High Performance Fuel Economy lubricant, specially adapted to FORD / JAGUAR / LAND ROVER vehicles

SPECIFICATIONS

Specifications :

- **ACEA C5**
- **API SN**
- **FORD WSS-M2C948-B**

OEM Approvals :

- **JAGUAR LAND ROVER STJLR.03.5004**

Recommandations :

- **ACEA A1/B1**
- **CHRYSLER MS 6395**
- **FIAT 9.55535-CR1**
- **FORD WSS-M2C925-A**
- **FORD WSS-M2C925-B**
- **FORD WSS-M2C945-A**
- **ILSAC GF-5**

PROPERTIES

SINTOLUX FORCE F 5W-20 is a high fuel economy lubricant. It brings advantages in terms of fuel savings and reduction of air pollution.

In addition, it has excellent properties against wear and excellent characteristics at low temperatures.

APPLICATIONS

SINTOLUX FORCE F 5W-20 has been in particular developed for use in the FORD Eco-boost engines, but it is also recommended for other vehicles such as CHRYSLER, JAGUAR ou LAND ROVER.

SINTOLUX FORCE F 5W-20 should be used in gasoline engines with or without turbochargers, and also in direct or indirect injection engines.

ADVANTAGES

- Very good thermal stability & resistance to oxydation, protects against sludge and deposits
- Durable fuel savings
- Very good cold start behaviour
- Decrease of oil consumption thanks to small losses due to volatility.
- Excellent protection against wear

TECHNICAL CHARACTERISTICS

| Average Characteristics | Unit | Average Value |
|-------------------------|--------------------|---------------|
| SAE Grade | | 5W-20 |
| Density at 15°C | kg/m ³ | 843 |
| Viscosity at 40°C | mm ² /s | 42 |
| Viscosity at 100°C | mm ² /s | 8 |
| Viscosity Index | | 157 |
| Flash Point | °C | 228 |