

SINTOLUX FORCE FR 5W-30

Low SAP Fuel Eco Engine Oil adapted in particular for Peugeot/Citroen & Renault/Nissan

SPECIFICATIONS

Specifications	ACEA C2/C3 API SP
Recommandations	FIAT 9.55535-S1 MB 226.52 / 229.31 / 229.51 / 229.52 PSA B71 2290 RENAULT RN17 RENAULT RN0700/0710

APPLICATIONS

Specially developed for Peugeot/Citroën & Renault/Nissan vehicles with exhaust after treatment and turbocharger, but can be used for other vehicles requiring the ACEA C2/C3 or API SP specifications.

SINTOLUX FORCE FR 5W-30 offers benefits to all advanced, fuel-efficient engines regardless of their emission category.

- Keeps turbochargers clean for maintaining long-term optimum charging pressure.
- Provides perfect protection of exhaust gas after treatment devices like DPF, CRT's or oxidation catalysts.
- Outstanding thermal stability and low sulphate ash levels maintain piston cleanliness regardless of the fuel.
- **SINTOLUX FORCE FR 5W-30** reduces fuel consumption significantly compared to conventional motor oils

PROPERTIES

- Very low levels of sulphated ash, phosphorous and sulphur protect.
- Extends the service time of all exhaust treatment systems
- Excellent protection against wear in advanced, highly-stressed Diesel and gasoline engines
- Reduces pollutant emissions
- Reduces the formation of deposits in engines and turbochargers.
- Low evaporation losses lower oil consumption
- Reduced fuel consumption of more than 2,5% compared to conventional oils

TECHNICAL CHARACTERISTICS

Average Characteristics	Unit	Average Value
SAE Grade		5W-30
Density at 15°C	kg/m ³	849
Viscosity at 100°C	mm ² /s	12
Viscosity at 40°C	mm ² /s	70,9
Viscosity Index		167
Pour Point	°C	-39
HTHS 150°C	mPas	≥ 3,6
Sulphated ashes	% m/m	< 0,75