

SINTOLUX FORCE V 0W-20

Ultra High Performance Extreme fuel-economy 100% Synthetic engine oil for light vehicles.

APPLICATIONS

SINTOLUX FORCE V 0W-20 was developed specifically for the new VW gasoline & diesel engines requiring the specifications VW 508.00/509.00 (« Blue oil »).

SINTOLUX FORCE V 0W-20 offers very high resistance against wear even in case of extended oil change intervals thanks to its PAO-based formula.

It is not backwards compatible with earlier VW specifications so must only be used in the engines requiring the specifications which it covers.

BENEFITS

- Fuel consumption reduced by 4% thanks to its low dynamic viscosity
- Reduced CO2 emissions
- Outstanding cold start performance
- Enables extended oil change intervals
- Very high resistance against wear

SPECIFICATIONS

Specifications	ACEA C5
Recommandations	FORD WSS M2C 956-A1 PORSCHE C20 VW 508.00 / 509.00

TECHNICAL CHARACTERISTICS

Characteristics	Unit	Average Value
SAE Grade		0W-20
Density at 15°C	g/ml	0.837
Kinematic viscosity at 100°C	mm ² /s	8.0
Kinematic viscosity at 40°C	mm ² /s	39.9
Viscosity Index		177
Pour Point	°C	-54
Sulphated Ash	Mm	< 0.8%
HTHS	mPa*s	>2.6 and < 2.9