

SINTOLUX FORCE V 0W-30

Low SAP Long drain Engine oil for VW-Audi and other vehicles

SPECIFICATIONS

Specifications : ACEA C3
API SN

Recommandations : BMW LONGLIFE-04
CHRYSLER MS-11106
FIAT 9.55535-S3
MB 229.31 / 229.51 / 229.52
PORSCHE C30
VW 504 00/507 00
BMW LONGLIFE-19 FE
RENAULT RN0700/0710

APPLICATIONS

SINTOLUX FORCE V 0W-30 was developed for VW Gasoline & Diesel engines and formulated for compatibility with exhaust after treatment devices and turbochargers, and to achieve outstanding Fuel Economy characteristics.

It can be used in VW vehicles recommending 0W-30 for extended oil drain intervals of 50.000 km or two years.

PROPERTIES

- Reduces ash formation in particulate filters and reduces fuel consumption.
- Increases the lifetime of particulate filters.
- Optimum cold starting, lower oil consumption and minimized exhaust emissions.

TECHNICAL CHARACTERISTICS

Average Characteristics	Unit	Average Value
SAE Grade		0W-30
Density at 15°C	kg/m ³	843
Viscosity at 100°C	mm ² /s	12.1
Viscosity at 40°C	mm ² /s	60.65
Viscosity Index		203
Pour Point	°C	- 51
Sulphated Ashes	%m/m	<1,5