

SINTOLUX FORCE V 5W-30

Low SAP Long drain Engine oil for VW-Audi and other vehicles

SPECIFICATIONS

Specifications :	ACEA C3 ACEA C2 (*) API SN
OEM approvals :	VW 504 00 / 507 00
Recommandations :	BMW LONGLIFE-04 CHRYSLER MS-11106 FIAT 9.55535-S3 MB 229.51/229.52 PORSCHE C30 RENAULT RN0700/0710

APPLICATIONS

SINTOLUX FORCE V 5W-30 was developed for VW Gasoline & Diesel engines and formulated for compatibility with exhaust after treatment devices and turbochargers, and to achieve outstanding Fuel Economy characteristics.

It can be used in VW vehicles after 2007 with extended oil drain intervals of 50.000 km or two years.

Many other engines, irrespectively of their make, can use this oil, in particular Diesel engines equipped with particulate filters.

(*) SINTOLUX FORCE V 5W-30 meets all the engine protection requirements of ACEA C2.

PROPERTIES

- Reduces ash formation in particulate filters and reduces fuel consumption.
- Increases the lifetime of particulate filters.
- Optimum cold starting, lower oil consumption and minimized exhaust emissions.

TECHNICAL CHARACTERISTICS

Average Characteristics	Unit	Average Value
SAE Grade		5W-30
Density at 15°C	kg/m ³	848
Viscosity at 100°C	mm ² /s	11.75
Viscosity at 40°C	mm ² /s	62.5
Viscosity Index		155
Flash Point	°C	238
Pour Point	°C	- 45



Les renseignements contenus dans cette notice sont donnés à titre indicatif. Nous nous réservons le droit d'apporter, sans préavis, toutes modifications à la formulation de nos produits dans le but d'en améliorer les performances ou de les mettre en conformité avec toute nouvelle et éventuelle réglementation les concernant.