

SINTOPOID 75W-80

Lubricant for mechanical transmissions

APPLICATION & ADVANTAGES

Lubricant for transmission, made with synthetic and mineral bases and EP additives.

SINTOPOID 75W-80 is dedicated for use in passenger cars gear-boxes.

SINTOPOID 75W-80 has been made to reduce started wear and to maintain high viscosity at high temperature even when it is used by long severe conditions.

SPECIFICATIONS

- ✓ API GL-4
- ✓ BMW 8322 (0309031 / 0403247 / 2339219 / 7533818)
- ✓ BMW 2300 (1434 404 / 7533 513 / 7533 818)
- ✓ FORD M2C200-C/C2/C3
- ✓ OPEL 19 40 182 / 757 / 768 / 776
- ✓ VOLVO 97308
- ✓ VW 501 50 (G 005 000 05/G 005 000/ G 005 000 20/G 052 911 A1/A2)

TECHNICAL CHARACTERISTICS

AVERAGE TECHNICAL CHARACTERISTICS	UNITS	AVERAGE VALUE	TEST METHOD
SAE Grade		75W-80	
Color	Yellow	Yellow	
Specific gravity at 20°C	kg/m ³	878	NFT 60101
Kinematic viscosity at 40°C	mm ² /s	50	NFT 60100
Kinematic viscosity at 100°C	mm ² /s	9,25	NFT 60100
Viscosity index		178	ASTM D97