

# **SINTOPOID LS 75W-90**

**Fully-synthetic multifunctional gear oil.**

**Suitable for axles and transfer gearboxes with or without self-locking differentials**

## **APPLICATIONS**

**SINTOPOID LS 75W-90** has been developed as gear oil with multifunctional application profile in passenger car applications.

Due to its unique additive technology and the high viscosity level **SINTOPOID LS 75W-90** can be used in highly loaded axles equipped with either conventional or limited slip differentials also as in most highly stressed manual transmissions in passenger car applications.

## **ADVANTAGES**

- Multifunctional application profile
- Good shifting comfort even in older transmissions
- Offers maximum wear protection for highly stressed hypoid drives
- Eliminates unpleasant axle noise (coasting load)
- Effectively prevents from noises when locking the LS-differential
- Extraordinarily thermally stable, i.e., it offers wear protection and security, as well as smooth operation, even at very high oil temperatures that occur during extended driving periods at maximum velocity

## **SPECIFICATIONS**

✓ API GL-4/ GL-5/ GL-5 including LS

✓ FORD M2C 200-C/C2

✓ VW G50/G51

## **TECHNICAL CHARACTERISTICS**

AVERAGE TECHNICAL CARACTERISTICS	UNITS	AVERAGE VALUE	TEST METHOD
SAE Grade		<b>75W-90</b>	
Density at 15°C	kg/m <sup>3</sup>	871	NFT 60101
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	126.5	DIN 51562-1
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	16.6	DIN 51562-1
Viscosity index		141	DIN ISO 2909
Flash Point	°C	202	DIN ISO 2592
Pour Point	°C	-48	DIN ISO 3016



Les renseignements contenus dans cette notice sont donnés à titre indicatif. Nous nous réservons le droit d'apporter, sans préavis, toutes modifications à la formulation de nos produits dans le but d'en améliorer les performances ou de les mettre en conformité avec toute nouvelle et éventuelle réglementation les concernant.